

2022

KLX[®]300R

Kawasaki
Let the Good Times Roll[®]

LIME GREEN



POWER

Engine	4-stroke single, DOHC, liquid-cooled
Displacement	292cc
Bore x Stroke	78.0 x 61.2mm
Compression Ratio	11.0:1
Fuel System	DFI [®] with 34mm Keihin throttle body
Ignition	TCBI Electronic Advance
Transmission	6-speed, return shift with wet multi-disc manual clutch
Final Drive	Chain

Rear Tire	100/100-18
Front Brakes	Single 270mm petal disc with a dual-piston caliper
Rear Brakes	Single 240mm petal disc with single-piston caliper

DETAILS

Frame Type	Tubular, Semi-Double Cradle
Rake/Trail	26.9° / 4.3 in
Overall Length	83.5 in
Overall Width	32.5 in
Overall Height	49.2 in
Ground Clearance	12.0 in / 11.8 CA model
Seat Height	36.4 in
Curb Weight	282.2 lb / 286.6 lb. CA model*
Fuel Capacity	2.1 gal
Wheelbase	56.5 in
Color Choices	Lime Green
Warranty	6 Months

PERFORMANCE

Front Suspension / Wheel Travel	43mm inverted telescopic fork with adjustable compression damping / 11.2 in
Rear Suspension / Wheel Travel	Uni-Trak [®] gas charged shock with piggyback reservoir with adjustable compression, rebound damping and spring preload / 11.2 in
Front Tire	80/100-21

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit chile.kawasaki-la.com for full product details.