KLX®300R







Single 270mm petal disc with a dual-

Single 240mm petal disc with single-

D	N	W	I E	D
Г	U	W	ľ	л

Engine 4-stroke single, DOHC, liquid-cooled

Displacement 292cc

Bore x Stroke 78.0 x 61.2mm

Compression

Ratio

11.0:1

Fuel System DFI® with 34mm Keihin throttle body

Ignition TCBI Electronic Advance

Transmission 6-speed, return shift with wet multi-disc

manual clutch

Final Drive Chain

Eramo Tyno

Ground

DETAILS

Rear Tire

Front Brakes

Rear Brakes

Frame Type Tubular, Semi-Double Cradle

100/100-18

piston caliper

piston caliper

Rake/Trail 26.9°/4.3 in

Overall Length 83.5 in

Overall Width 32.5 in

Overall Height 49.2 in

Clearance

Seat Height 36.4 in

Curb Weight 282.2 lb / 286.6 lb. CA model*

12.0 in / 11.8 CA model

Fuel Capacity 2.1 gal

Wheelbase 56.5 in

Color Choices Lime Green

Warranty 6 Months

PERFORMANCE

Front
Suspension /
Wheel Travel

43mm inverted telescopic fork with adjustable compression damping /11.2 in

Rear Suspension / Wheel Travel Uni-Trak® gas charged shock with piggyback reservoir with adjustable compression, rebound damping and

spring preload/11.2 in

Front Tire 80/100-21



