MULE™ 4010 4x4









6.9 in

800 lb

1327 lb

POWER

4-stroke, 2-cylinder, OHV, 90° V Liquid-cooled **Engine**

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2500 rpm

Bore x Stroke 2.99x2.68 in

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with

(H,L,N,R)

Final Drive

differential with differential lock

Engine Braking

Alternator Output 23 amp

(max)

Selectable 2WD/4WD, shaft. Dual mode rear

CAPABILITY

Front Suspension / MacPherson Strut/3.9 in **Wheel Travel**

Rear Suspension / Wheel Travel

DeDion Axle/2.8 in

Front Tires 23x11.00-10 **Rear Tires** 23x11.00-10

Steering Electric Power Steering (EPS)

Park Brake Type Independent, Mechanical Drum

Front Brakes Drum **Rear Brakes** Drum

Fuel Capacity 6.3 gal

Turning Radius 11.2 ft

46.3 x 51.6 x 11.4 in **Cargo Bed Dimensions**

Cargo Bed Load Capacity

Payload Capacity

(LxWxH)

Ground Clearance

Seating Capacity

Towing Capacity 1200 lb

Lighting (2) Halogen headlights (2) tail/brake lights

DETAILS

Overall Length 116.7 in

Overall Width 62.0 in

Overall Height 75.8 in

Curb Weight 1433.3 lb*

Wheelbase 73.6 in

Instruments Parking brake warning light, coolant temperature

warning light, 12V DC outlet, fuel gauge, hour meter

Wheel Type Steel

Color Choices Timberline Green, Dark Royal Red

Warranty Kawasaki 3-Year Limited Warranty



