
MULE SX™ 4x4 FI









4.2 gal

399 lb

POWER

Engine 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

Maximum Torque 21.4 lb-ft @ 2400 rpm

Bore x Stroke 3.23x2.99 in

Compression Ratio 8.6:1

Fuel System Fuel Injection

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking No

Alternator Output 22.9 amp

(max)

Ground Clearance 6.7 in

Turning Radius 10.8 ft

Cargo Bed

Fuel Capacity

Dimensions (LxWxH)

Cargo Bed Load

Capacity

Payload Capacity 915 lb

Seating Capacity

Towing Capacity 1100 lb*

Lighting (2) Halogen headlights, tail/brake lights

35.6 x 40.9 x 9.6 in

CAPABILITY

Front Suspension / N
Wheel Travel

MacPherson Strut/3.1 in

Rear Suspension / Wheel Travel

Unit Swingarm/3.1 in

Front Tires 24x9.00-10

Rear Tires 24x11.00-10

Steering Rack-and-pinion

Park Brake Type Independent, Mechanical Drum

Front Brakes Drum

Rear Brakes Drum

DETAILS

Overall Length 106.7 in

Overall Width 52.6 in

Overall Height 70.9 in

Curb Weight 1031.9 lb**

Wheelbase 70.1 in

Instruments Fuel gauge, hour meter, oil temp light, parking brake

light / horn (SE only)

Wheel Type Stee

Color Choices Timberline Green, Dark Royal Red

Warranty Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



*Requires Optional Hitch

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit chile.kawasaki-la.com for full product details.