KLR®650 TRAVELER ABS







P	N	V	V	F	R
	u	1		L	•

Engine 4-Stroke, single cylinder, DOHC

Displacement 652cc

Bore x Stroke 100.0 x 83.0mm

Compression Ratio

Ratio

9.8:1

Maximum Torque

39.1 lb.-ft. @ 4,500rpm

Fuel System

DFI w/40mm Throttle Body

Ignition

CDI

Transmission

5-speed, return shift with wet multi-disc

manual clutch

Final Drive

Sealed Chain

PERFORMANCE

Front
Suspension /
Wheel Travel

41mm telescopic fork/ 7.9 in

Rear Suspension / Wheel Travel Uni-Trak®, single shock with adjustable rebound damping and adjustable spring

preload / 8.0 in

Front Tire 90/90-21

Rear Tire 130/80-17

Front Brakes Single 300mm disc with 2-piston calipers,

ABS

Rear Brakes Single 240mm disc with single-piston

caliper, ABS

DETAILS

Frame Type Tubular, Semi-Double Cradle

Rake/Trail 30.0°/4.8 in

Overall Length 89.8 in

Overall Width 38.2 in

Overall Height 57.7/56.3 in (screen hi/lo)

Ground 8.3 in Clearance

Seat Height 34.3 in

Curb Weight 471.7 lb*

Fuel Capacity 6.1 gal

Wheelbase 60.6 in

Color Choices Pearl Solar Yellow

Warranty 12 Months



