²⁰²³ NINJA[®] ZX[™]-10R





METALLIC MATTE GRAPHENESTEEL GRAY/ METALLIC DIABLO BLACK



POWER

Engine4-stroke, In-Line Four, DOHC, 16-valve, liquid- cooledDisplacement998ccBore x Stroke76.0 x 55.0mmCompression Ratio13.0:1Fuel SystemDFI® w/47mm Mikuni throttle bodies (4) with oval sub-throttles, two injectors per cylinderIgnitionTCBI with digital advance and Sport-Kawasaki TRaction Control (S-KTRC)Final DriveSealed chainElectronic Rider AidsElectronic Cruise Control, Kawasaki Launch Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management Function (KCMF)		
Bore x Stroke76.0 x 55.0mmCompression Ratio13.0:1Fuel SystemDFI® w/47mm Mikuni throttle bodies (4) with oval sub-throttles, two injectors per cylinderIgnitionTCBI with digital advance and Sport-Kawasaki TRaction Control (S-KTRC)Transmission6-speed, return shiftFinal DriveSealed chainElectronic Rider AidsElectronic Cruise Control, Kawasaki Launch Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management	Engine	
Compression Ratio13.0:1Fuel SystemDFI® w/47mm Mikuni throttle bodies (4) with oval sub-throttles, two injectors per cylinderIgnitionTCBI with digital advance and Sport-Kawasaki TRaction Control (S-KTRC)Transmission6-speed, return shiftFinal DriveSealed chainElectronic Rider AidsElectronic Cruise Control, Kawasaki Launch Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management	Displacement	998cc
RatioFuel SystemDFI® w/47mm Mikuni throttle bodies (4) with oval sub-throttles, two injectors per cylinderIgnitionTCBI with digital advance and Sport-Kawasaki TRaction Control (S-KTRC)Transmission6-speed, return shiftFinal DriveSealed chainElectronic Rider AidsElectronic Cruise Control, Kawasaki Launch Control Mode (KLCM), Kawasaki Sport TRaction Control, Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management	Bore x Stroke	76.0 x 55.0mm
sub-throttles, two injectors per cylinderIgnitionTCBI with digital advance and Sport-Kawasaki TRaction Control (S-KTRC)Transmission6-speed, return shiftFinal DriveSealed chainElectronic Rider AidsElectronic Cruise Control, Kawasaki Launch Control Mode (KLCM), Kawasaki Sport TRaction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management	-	13.0:1
TRaction Control (S-KTRC)Transmission6-speed, return shiftFinal DriveSealed chainElectronic Rider AidsElectronic Cruise Control, Kawasaki Launch Control Mode (KLCM), Kawasaki Sport TRaction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management	Fuel System	
Final DriveSealed chainElectronic Rider AidsElectronic Cruise Control, Kawasaki Launch Control Mode (KLCM), Kawasaki Sport TRaction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management	Ignition	U
Electronic Rider Aids Electronic Cruise Control, Kawasaki Launch Control Mode (KLCM), Kawasaki Sport TRaction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management	Transmission	6-speed, return shift
Aids Control Mode (KLCM), Kawasaki Sport TRaction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management	Final Drive	Sealed chain
	Eteeti onne nuder	Control Mode (KLCM), Kawasaki Sport TRaction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management

PERFORMANCE

Front Suspension / Wheel Travel	43mm inverted Balance Free Fork, adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in
Rear Suspension / Wheel Travel	Horizontal back-link with Balance Free gas- charged shock, stepless, dual-range (low-/high- speed) compression damping, stepless rebound damping, fully adjustable spring preload/4.5 in

Front Tire	120/70 ZR17
Rear Tire	190/55 ZR17
Front Brakes	Brembo® dual semi-floating 330mm discs with dual radial-mounted monobloc 4-piston calipers
Rear Brakes	Single 220mm disc with aluminum single-piston caliper

DETAILS

Frame Type	Aluminum perimeter
Rake/Trail	25.0°/4.1 in
Overall Length	82.1 in
Overall Width	29.5 in
Overall Height	46.7 in
Ground Clearance	5.3 in
Seat Height	32.9 in
Curb Weight	452.0 lb*
Fuel Capacity	4.5 gal
Wheelbase	57.1 in
Special Features	4.3" Full-Color TFT Instrumentation, Smartphone Connectivity via RIDEOLOGY THE APP
Color Choices	Metallic Matte Graphenesteel Gray/Metallic Diablo Black
Warranty	12 Month Limited Warranty



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit chile.kawasaki-la.com for full product details.