## KLX<sup>®</sup>230SM ABS







P	N	V	V	FI	R
	u	$\mathbf{A}^{\prime}$	٧ı	LI	М

**Engine** 4-stroke single, SOHC, air-cooled

**Displacement** 233cc

**Bore x Stroke** 67.0 x 66.0mm

Compression

Ratio

Maximum **Torque** 

13.2 lb-ft @ 6,400 rpm

**Fuel System** 

Ignition

9.4:1

Transmission 6-speed

**Final Drive** 

**Electronic Rider** 

**Aids** 

DFI® with dual 32mm throttle bodies

TCBI with Electronic Advance

Sealed chain

Anti-lock Brake System (ABS)

## **PERFORMANCE**

37mm inverted fork/7.4 in **Front** Suspension / **Wheel Travel Rear Suspension** Uni-Trak® linkage system and single shock with adjustable spring preload/8.7 in / Wheel Travel **Front Tire** 110/70-17

Single 300mm petal disc with a dual-piston **Front Brakes** caliper and ABS

Single 220mm petal disc with single-piston **Rear Brakes** 

caliper and ABS

## **DETAILS**

Perimeter, high-tensile steel **Frame Type** 24.9°/3.0 in Rake/Trail

**Overall Length** 80.1 in

**Overall Width** 33.2 in

44.2 in **Overall Height** 

8.6 in Ground

Clearance

**Seat Height** 33.0 in

**Curb Weight** 299.8/302.0 lb\* 50-State Model

**Fuel Capacity** 2.0 gal

Wheelbase 53.7 in

**Special Features** ERGO-FIT®, LCD Instrumentation with

Smartphone Connectivity via RIDEOLOGY THE

APP MOTORCYCLE

**Color Choices Battle Gray** 

Warranty 12 Month Limited Warranty



**Rear Tire** 



120/70-17