## <sup>2024</sup> **KX<sup>™</sup>450**







## **POWER**

4-stroke single, DOHC, liquid-cooled
449cc
96.0 x 62.1mm
12.5:1
DFI® with 44mm Keihin throttle body
Digital CDI with handlebar-controlled Power Modes
5-speed, return shift, with wet multi-disc manual clutch and hydraulic clutch actuation
Chain
Power Modes, Kawasaki TRaction Control (KTRC), Launch Control Mode

## PERFORMANCE

Front Suspension / Wheel Travel	49mm inverted telescopic coil-spring fork with 21- way adjustable compression and 22-way adjustable rebound damping/12.0 in
Rear Suspension / Wheel Travel	Uni-Trak® gas charged shock with piggyback reservoir with adjustable dual-range compression damping (19-way low speed and 4.25 turn stepless high speed), 23-way adjustable rebound damping and stepless adjustable preload/12.1 in

Front Tire	80/100-21
Rear Tire	120/80-19
Front Brakes	Single semi-floating 270mm Braking/Sunstar petal disc with Brembo master cylinder and dual- piston caliper
Rear Brakes	Single 240mm Braking/Sunstar petal disc with single-piston caliper

## DETAILS

Frame Type	Aluminum perimeter
Rake/Trail	26.6°/4.5 in
Overall Length	85.8 in
Overall Width	32.3 in
Overall Height	50.0 in
Ground Clearance	13.6 in
Seat Height	37.8 in
Curb Weight	238.3 lb* without fuel / 248.2 lb*
Fuel Capacity	1.64 gal
Wheelbase	58.3 in
Special Features	Smartphone Connectivity via RIDEOLOGY THE APP
Color Choices	Lime Green
Warranty	Not Available





\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit chile.kawasaki-la.com for full product details.