## NINJA® ZX™-6R







METALLIC FLAT SPARK BLACK/EBONY



PEARL ROBOTIC WHITE/METALLIC GRAPHITE GRAY



180/55 ZR17

(ABS only)

System (KIBS) (ABS only)

P	0	١	N	Æ	łR	

Engine 4-stroke, In-Line Four, DOHC, 16-valve, liquid-

cooled

12.9:1

Displacement 636cc

Bore x Stroke 67.0 x 45.1mm

Compression

Ratio

. . . .

**Fuel System** DFI® with 38mm Keihin throttle bodies (4) and oval

sub-throttles

Ignition TCBI with Electronic Advance

Transmission 6-speed, return shift

Final Drive Sealed chain

**Electronic Rider** 

Aids

Kawasaki TRaction Control (KTRC), Power Modes (Full/Low), Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only), Kawasaki Quick Shifter

(KQS) (upshift only)

## **DETAILS**

**Rear Tire** 

**Front Brakes** 

**Rear Brakes** 

Frame Type Aluminum perimeter

Rake/Trail 23.5°/4.0 in

Overall Length 79.7 in

Overall Width 28.0 in

Overall Height 43.3 in

**Ground Clearance** 5.1 in

Seat Height 32.7 in

Curb Weight 436.6 lb\* (ABS), 432.2 lb\* (non-ABS) 50-State Model,

434.4 lb\* (ABS), 430.0 lb\* (non-ABS) 49-State Model

Dual semi-floating 310mm discs with dual radialmounted, monobloc, opposed 4-piston caliper,

Kawasaki Intelligent anti-lock Brake System (KIBS)

Single 220mm petal discs with single-piston

caliper, Kawasaki Intelligent anti-lock Brake

Fuel Capacity 4.5 gal

Wheelbase 55.1 in

**Special Features** 4.3" Full-Color TFT Instrumentation, Smartphone

Connectivity via RIDEOLOGY THE APP

**Color Choices** Metallic Flat Spark Black/Ebony, Pearl Robotic

White/Metallic Graphite Gray

Warranty 12 Month Limited Warranty

## **PERFORMANCE**

Front Suspension / Wheel Travel

41mm inverted fork (SFF-BP) with rebound and compression damping and spring preload adjustability, and top-out springs /4.7 in

Rear Suspension / Wheel Travel Bottom-link Uni-Trak® with gas-charged shock, stepless compression damping adjustment, stepless adjustable rebound damping, fully

adjustable spring preload/5.9 in

**Front Tire** 

120/70 ZR17

Scan with camera to view videos, key features and more.

