ELEKTRODE® 20









POWER

Motor Type Air-cooled, brushless, in-wheel **Power Modes** 3 modes (High / Mid / Low) Max Speed by Mode -24 mph / 24 mph / 13 mph H/M/L

Battery Type Lithium-ion (in-frame) Battery Voltage/ 50.4 V 10.2 Ah (514.1 Wh) Capacity

Battery Charge Time 4 hours (approx)*

Drive System Direct hub motor, chainless

Battery Rated Output 750 W

Battery Running Time Low: 180 minutes / High: 60 minutes

Aluminum

Maximum Battery Charge Cycles

Rear Suspension/

Wheel Travel

500 (after which 80% of original charge capacity)

PERFORMANCE

Frame Type Front Suspension/ 28mm telescopic fork / 50mm

Wheel Travel

28mm telescopic fork / 50mm

Front Tire 20 x 2.125 **Rear Tire** 20 x 2.125

Front Brakes 160mm mechanical disc 160mm mechanical disc **Rear Brakes**

Handlebar Clamp Size Steering Stem Size 28.6mm

22.2mm

Seat Post Size

27.2mm

DETAILS

Rake & Trail 25 deg / 2.95 in (75mm)

Overall Length 59.3 in (1,505mm) **Overall Width** 26.3 in (668mm) 36.6 in (929mm) **Overall Height**

Ground Clearance 7.1 in (181mm)

Seat Height 21.6-27.3 in (550-693mm)

38.93 in (989mm) Wheelbase **Curb Weight** 46.1 lb (20.9 kg) **Color Choices** Lime Green, Black

Appropriate Rider's

Rider Weight (max) 132 lb (60 kg)

Yes (rotating pedal, foldable) **Footrest**

Charging power

source

110-V AC (Home)

Front of bike **Charging connector Number plate** STD, MX-Style

WARRANTY

Frame and Fork TBA Non-Electrical TBA Components **Electric System** TBA

Components **Normal Wear and**

Tear Items

TBA

Scan with camera to view videos, key features and more.

