2025 ELIMINATOR®







POWER		Front Brakes	Single 310mm disc with twin-piston caliper (and ABS)
Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled	Rear Brakes	Single 220mm disc with single-piston caliper (and ABS)
Displacement	451cc		
Bore x Stroke	70.0 x 58.6mm	DETAILS	
Compression Ratio	11.3:1	Frame Type	Trellis, high-tensile steel
Maximum Torque	31.7 lb-ft @ 7,500 rpm	Rake/Trail	30.0°/4.8 in
Fuel System	DFI® with 32mm throttle bodies	Overall Length	88.6 in
Ignition	TCBI w/ Digital Advance	Overall Width	30.9 in
Transmission	6-speed, return shift	Overall Height	43.3 in
Final Drive	Sealed chain	Ground Clearance	5.9 in
Electronic Rider Aids	Anti-lock Brake System (ABS only)	Seat Height	28.9 in
PERFORMANCE		Estimated Dry Weight	361.6 lb** (ABS) / 359.4 lb** (non-ABS)
-		Curb Weight	388.1 lb* (ABS) / 385.9 lb* (non-ABS)
Front Suspension / Wheel Travel	41mm telescopic fork/4.7 in	Fuel Capacity	3.4 gal
wheet fravet		Wheelbase	59.8 in
Rear Suspension / Wheel Travel	Twin shocks/3.1 in	Special Features	ERGO-FIT®, Smartphone Connectivity via RIDEOLOGY THE APP
Front Tire	130/70-18	Color Choices	Metallic Flat Spark Black, Pearl Sand Khaki
Rear Tire	150/80-16	Warranty	12 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit chile.kawasaki-la.com for full product details.