

2025

# KLX<sup>®</sup>110R L

**Kawasaki**  
Let the Good Times Roll<sup>®</sup>



## POWER

<b>Engine</b>	4-stroke, single-cylinder, SOHC, air-cooled
<b>Displacement</b>	112cc
<b>Bore x Stroke</b>	53.0 x 50.6mm
<b>Compression Ratio</b>	9.5:1
<b>Fuel System</b>	Keihin PB18 carburetor and screw type throttle limiter on grip housing
<b>Ignition</b>	DC-CDI
<b>Transmission</b>	4-speed, return shift, wet multi-disc manual clutch
<b>Final Drive</b>	Chain

<b>Front Tire</b>	2.50 x 14
<b>Rear Tire</b>	3.00 x 12
<b>Front Brakes</b>	90mm mechanical drum, cable actuated
<b>Rear Brakes</b>	110mm mechanical drum, rod actuated

## PERFORMANCE

<b>Front Suspension / Wheel Travel</b>	30mm hydraulic telescopic fork/5.5 in
<b>Rear Suspension / Wheel Travel</b>	Swingarm with single hydraulic shock/5.2 in

## DETAILS

<b>Frame Type</b>	Backbone frame, high-tensile steel
<b>Rake/Trail</b>	24.2° / 1.9 in
<b>Overall Length</b>	61.4 in
<b>Overall Width</b>	25.6 in
<b>Overall Height</b>	39.0 in
<b>Ground Clearance</b>	10.4 in
<b>Seat Height</b>	28.7 in
<b>Curb Weight</b>	167.5 lb*
<b>Fuel Capacity</b>	1.0 gal
<b>Wheelbase</b>	42.3 in
<b>Color Choices</b>	Lime Green, Battle Gray
<b>Warranty</b>	6 Month Limited Warranty

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [chile.kawasaki-la.com](http://chile.kawasaki-la.com) for full product details.