


2025

KLX[®]140R



POWER

Engine	4-stroke, single-cylinder, SOHC, air-cooled
Displacement	144cc
Bore x Stroke	58.0 x 54.4mm
Compression Ratio	9.5:1
Fuel System	Keihin PB20 carburetor
Ignition	Digital DC-CDI
Transmission	5-speed, return shift, with wet multi-disc manual clutch
Final Drive	Chain

PERFORMANCE

Front Suspension / Wheel Travel	33mm telescopic fork/7.1 in
Rear Suspension / Wheel Travel	Uni-Trak [®] linkage system and single shock with 5-way preload adjustability/7.1 in
Front Tire	70/100-17

Rear Tire	90/100-14
Front Brakes	Single 220mm petal disc with a dual-piston caliper
Rear Brakes	Single 186mm petal disc with single-piston caliper

DETAILS

Frame Type	High-tensile steel, box-section perimeter
Rake/Trail	27.0°/3.3 in
Overall Length	71.7 in
Overall Width	31.1 in
Overall Height	41.3 in
Ground Clearance	9.3 in
Seat Height	30.7 in
Curb Weight	205.0 lb*
Fuel Capacity	1.5 gal
Wheelbase	49.6 in
Color Choices	Lime Green, Battle Gray
Warranty	6 Month Limited Warranty

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit chile.kawasaki-la.com for full product details.