²⁰²⁵ **KLX®140R F**







POWER		Rear Tire	4.10 x 18
Engine 4-stroke, single-cylinder, SOHC, air-cooled		Front Brakes	Single 220mm petal disc with a dual- piston caliper
-		Rear Brakes	Single 186mm petal disc with single-
Displacement	144cc	Real Drakes	piston caliper
Bore x Stroke	58.0 x 54.4mm	DETAIL O	
Compression Ratio	9.5:1	DETAILS	
Fuel System	Keihin PB20 carburetor	Frame Type	High-tensile steel, box-section perimeter
Ignition	Digital DC-CDI	Rake/Trail	27.0°/4.6 in
Transmission	5-speed, return shift, with wet multi-disc manual clutch	Overall Length	78.9 in
		Overall Width	31.1 in
Final Drive	Chain	Overall Height	44.7 in
PERFORMANCE		Ground Clearance	12.4 in
Front	33mm telescopic fork/7.5 in	Seat Height	33.9 in
Suspension / Wheel Travel		Curb Weight	218.2 lb*
Rear	Uni-Trak [®] linkage system and single shock	Fuel Capacity	1.5 gal
Suspension / Wheel Travel	with piggyback reservoir, 20-way rebound damping and threaded preload	Wheelbase	52.4 in
	adjustability/7.9 in	Color Choices	Lime Green, Battle Gray
Front Tire	2.75 x 21	Warranty	6 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit chile.kawasaki-la.com for full product details.