KLX®230R









100/100-18

piston caliper

piston caliper

Single 240mm petal disc with a dual-

Single 220mm petal disc with single-

POWER

Engine 4-stroke, single-cylinder, SOHC, air-cooled
Displacement 233cc
Bore x Stroke 67.0 x 66.0mm
Compression Ratio 9.4:1

Fuel System DFI® with 32mm Keihin throttle body

TCBI with electronic advance

Transmission 6-speed, return shift with wet multi-disc manual clutch

Final Drive Chain

DETAILS

Rear Tire

Front Brakes

Rear Brakes

High-tensile steel, box-section perimeter **Frame Type** Rake/Trail 25.4° / 4.2 in **Overall Length** 80.5 in **Overall Width** 33.3 in **Overall Height** 47.2 in Ground 11.4 in Clearance **Seat Height** 35.6 in **Curb Weight** 262.4 lb* / 264.5 lb* 50-State Model

Lime Green, Battle Gray

6 Month Limited Warranty

1.7 gal

54.1 in

PERFORMANCE

Suspension / Wheel Travel

Rear
Suspension / Uni-Trak® linkage system and single shock with adjustable spring preload/9.8 in

Wheel Travel

Front Tire

37mm telescopic fork/9.8 in

Uni-Trak® linkage system and single shock with adjustable spring preload/9.8 in





Fuel Capacity

Color Choices

Wheelbase

Warranty