MULE[™] 4010 4x4 FE







POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2,500 rpm

Bore x Stroke 76.0 x 68.0mm

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking N

Alternator Output 23 amp

(max)

6.9 in

800 lb

Fuel Capacity 6.3 gal

Turning Radius 11.2 ft

Cargo Bed

Ground Clearance

Dimensions (LxWxH)

Cargo Bed Load

Capacity

Payload Capacity 1,312 lb

Seating Capacity 2

Towing Capacity 1,200 lb

Lighting (2) Halogen headlights, (2) tail/brake lights

46.3 x 51.6 x 11.4 in

CAPABILITY

Front Suspension / MacPherson Strut/3.9 in Wheel Travel

Rear Suspension / DeDion Axle/2.8 in Wheel Travel

 Front Tires
 23 x 11-10

 Rear Tires
 23 x 11-10

Steering Rack-and-pinion w/ Electric Power Steering (EPS)

Park Brake Type Independent, mechanical drum

Front Brakes Drum

Rear Brakes Drum

DETAILS

Overall Length 116.7 in

Overall Width 62.0 in

Overall Height 78.1 in

Curb Weight 1,448.7 lb*

Wheelbase 73.6 in

Instruments Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter

Additional Features Roof, Horn, Universal Key, High Visibility Orange

Seatbelts

Color Choices Bright White

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



