2025

NINJA® 500







METALLIC MATTE WHITISH SILVER/METALLIC MOONDUST GRAY



PASSION RED/METALLIC FLAT SPARK BLACK/ METALLIC MATTE DARK GRAY



METALLIC FLAT SPARK BLACK/METALLIC SPARK BLACK/METALLIC MOONDUST GRAY



POWER

Engine 4-stroke, Parallel Twin, DOHC, liquid-cooled

Displacement 451cc

70.0 x 58.6mm

Compression

Bore x Stroke

Ratio

11.3:1

Maximum Torque

31.7 lb-ft @ 7,500 rpm

Fuel System

DFI® with dual 32mm throttle bodies

Ignition

TCBI with Digital Advance

Transmission

6-speed

Final Drive

Sealed chain

Electronic Rider

Economical Riding Indicator, Anti-lock Brake System

Aids

(ABS only)

PERFORMANCE

Front Suspension / Wheel Travel

41mm hydraulic telescopic fork/4.7 in

Rear Suspension / Wheel Travel

Horizontal back-link with adjustable spring

preload/5.1 in

Front Tire

110/70-17

Rear Tire

150/60-17

Front Brakes

Single 310mm semi-floating disc with 2-piston

calipers (and ABS)

Rear Brakes

Single 220mm disc with single-piston caliper (and ABS)

DETAILS

Frame Type Trellis, high-tensile steel

Rake/Trail 24.5°/3.6 in

Overall Length 78.5 in

Overall Width 28.7 in

Overall Height 44.1 in

Ground Clearance 5.7 in

Seat Height 30.9 in

Estimated Dry

Weight

344.0 lb** (ABS) / 346.2 lb** (ABS) 50-State Model, 339.6 lb** (non-ABS) / 341.8 lb** (non-ABS) 50-State

Model

Curb Weight

374.9 lb*(ABS) / 377.1 lb* (ABS) 50-State Model, 370.4 lb* (non-ABS) / 372.6 lb* (non-ABS) 50-State Model

Fuel Capacity 3.7 gal

Wheelbase 54.1 in

Special Features

 ${\sf ERGO\text{-}FIT}^{\texttt{\$}}, \ {\sf LCD} \ Instrumentation \ with \ {\sf Smartphone}$

Connectivity via RIDEOLOGY THE APP

Color Choices

Metallic Matte Whitish Silver/Metallic Moondust Gray, Passion Red/Metallic Flat Spark Black/ Metallic Matte Dark Gray, Metallic Flat Spark Black/ Metallic Spark Black/Metallic Moondust Gray

Warranty 12 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit chile.kawasaki-la.com for full product details.