TERYX® KRX4™ 1000 BLACKOUT EDITION







I		N	l	N	F	R
	- 1	w		м		

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 999cc

Maximum Torque 76.7 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 11.5:1

Fuel System DFI® with (2) 50mm throttle bodies

Ignition TCBI with Electronic Advance

Starting System Electri

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes

CAPABILITY

Front Suspension / Wheel Travel Double wishbone, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable

compression damping/18.6 in

Rear Suspension / 4-link trailing-arm rear suspension, FOX 2.5 PODIUM LSC shocks With piggyback reservoir, fully adjustable preload, and 24-

position adjustable compression damping/21.1 in

Front Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Rear Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Steering Electric Power Steering (EPS) / rack-and-pinion

Front Brakes Dual hydraulic discs with 2-piston calipers

Rear Brakes Dual hydraulic discs with single-piston calipers

Ground Clearance 13.8 in (max), 13.2 in (std)

Fuel Capacity 10.6 gal
Turning Radius 23.3 ft

Cargo Bed Dimensions 14.6 x 33.1 x 9.1 in (LxWxH)

Cargo Bed Load

Capacity

Payload Capacity 1,001 lb

Seating Capacity 4

Towing Capacity N/A

Lighting (2) LED headlights, (2) LED taillights, LED stoplight, (4) LED light

bars

351 lh

DETAILS

Frame Ladder type, tubular steel

FLAT EBONY

Overall Length 160.4 in
Overall Width 68.1 in
Overall Height 78.0 in

Curb Weight 2,253.5 lb* / 2,257.7 lb* CA Model

Wheelbase 125.8 in

Instruments Multi-function digital meter with bar-style tachometer (2

display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning

Additional Features LED light bars (38-in mounted to front of roof, 8-in mounted to front bumper, (2) 8-in mounted to rear of roof), Front Bumper,

lamp, and CVT belt warning lamp

Rear Bumper, Steel skid-plates w/ drain holes, KQR™ Premium Roof, Hifonics® Audio System, WARN® VRX 45 Powersport Winch

Color Choices Flat Ebony

Warranty 6 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A.