

2025

VULCAN® S



- METALLIC MATTE GRAPHITE GRAY/
METALLIC MATTE CARBON GRAY
- METALLIC FLAT SPARK BLACK



POWER

Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled
Displacement	649cc
Bore x Stroke	83.0 x 60.0mm
Compression Ratio	10.8:1
Maximum Torque	46.3 lb-ft @ 6,600 rpm
Fuel System	DFI® with 38mm throttle bodies (2), with sub-throttle valves
Ignition	TCBI with Electronic Advance
Transmission	6-speed with positive neutral finder
Final Drive	Sealed chain
Electronic Rider Aids	Economical Riding Indicator, Anti-lock Brake System (ABS)

PERFORMANCE

Front Suspension / Wheel Travel	41mm telescopic fork/5.1 in
Rear Suspension / Wheel Travel	Lay-down offset rear shock with linkage and adjustable preload/3.2 in
Front Tire	120/70-18

Rear Tire	160/60-17
Front Brakes	Single 300mm disc with twin-piston caliper (and ABS)
Rear Brakes	Single 250mm disc with single-piston caliper (and ABS)

DETAILS

Frame Type	High-tensile steel diamond frame
Rake/Trail	31° /4.7 in
Overall Length	90.9 in
Overall Width	34.6 in
Overall Height	43.3 in
Ground Clearance	5.1 in
Seat Height	27.8 in
Curb Weight	498.3 lb* (ABS), 491.7 lb* (non-ABS)
Fuel Capacity	3.7 gal
Wheelbase	62.0 in
Special Features	ERGO-FIT®
Color Choices	Metallic Matte Graphite Gray/Metallic Matte Carbon Gray, Metallic Flat Spark Black
Warranty	12 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit chile.kawasaki-la.com for full product details.