

2025

Z900 SE ABS

Kawasaki
Let the Good Times Roll®



METALLIC MATTE GRAPHITE GRAY/EBONY/
METALLIC GRAPHITE GRAY



POTENCIA

Motor	4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled
Cilindrada	948cc
Diámetro por carrera	73.4 x 56.0mm
Relación de compresión	11.8:1
Potencia máxima	123.0 hp ¹ @ 9,500 rpm
Par motor máximo	73.1 lb-ft @ 7,700 rpm
Sistema de combustible	DFI® with 36mm throttle bodies
Encendido	TCBI with Electronic Advance
Transmisión	6-speed, return shift
Transmisión final	Sealed chain
Asistencia electrónica para el piloto	Economical Riding Indicator, Electronic Cruise Control, Kawasaki TRaction Control (KTRC), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-Enhanced Chassis Orientation Awareness

RENDIMIENTO

Suspensión delantera/recorrido del neumático	41mm inverted telescopic fork with compression and rebound damping and spring preload adjustability/4.7 in
Suspensión trasera/recorrido del neumático	Horizontal back-link, Öhlins S46 gas-charged rear shock with rebound damping and spring preload adjustability/5.5 in
Neumático delantero	120/70-17

Neumático trasero	180/55-17
Frenos delanteros	Dual 300mm semi-floating discs with radial-mount 4-piston Brembo M4.32 monobloc calipers and ABS
Frenos traseros	Single 250mm disc with single-piston caliper and ABS

DETALLES

Tipo de chasis	Trellis, high tensile steel
Ángulo de dirección/Avance	24.7° / 4.3 in
Largo total	81.3 in
Ancho total	32.7 in
Altura del asiento	44.7 in
Distancia al suelo	5.7 in
Altura del asiento	31.9 in
Peso seco estimado	425.6 lb** / 427.8 lb** 50-State Model
Peso en orden de marcha	469.7 lb* / 471.9 lb* 50-State Model
Depósito de combustible	4.5 gal
Distancia entre ejes	57.1 in
Características especiales	5" All-digital TFT color instrumentation, All-LED lighting, USB Type-C outlet, ERGO-FIT®, Smartphone Connectivity with available Voice Command and Turn-by-Turn Navigation via RIDELOGY THE APP MOTORCYCLE***
Colores disponibles	Metallic Matte Graphite Gray/Ebony/Metallic Graphite Gray
Garantía	12 Month Limited Warranty

Escanear con cámara para ver videos, características clave y más.



^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.
^{**}Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
^{***}RIDELOGY THE APP and all trademarks, registered trademarks, logos, and copyrights are the property of their respective owners. Voice command and navigation functions will be available only to users who have purchased a license for those functions. Feature availability may vary to meet individual markets.
¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visite chile.kawasaki-la.com para obtener detalles completos del producto.