

ACTUALIZADA 2025

NINJA H2® SX SE ABS

Kawasaki
Let the Good Times Roll®



EMERALD BLAZED GREEN/METALLIC DIABLO BLACK/
METALLIC MATTE GRAPHENE STEEL GRAY



POTENCIA

Motor	4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled
Cilindrada	998cc
Diámetro por carrera	76.0 x 55.0mm
Relación de compresión	11.2:1
Maximum Horsepower	207.0 hp ¹ @ 10,000 rpm
Par motor máximo	101.0 lb-ft @ 8,500 rpm
Sistema de combustible	DFI® with 40mm throttle bodies (4); Kawasaki Supercharger
Encendido	TCBI with Digital Advance
Transmisión	6-speed, return shift, dog-ring
Transmisión final	Sealed chain
Asistencia electrónica para el piloto	Economical Riding Indicator, Advanced Rider Assistance Systems (ARAS): Forward Collision Warning (FCW), Blind-Spot Detection (BSD), Adaptive Cruise Control (ACC), Vehicle Hold Assist (VHA), Kawasaki Electronic Control Suspension with Showa Skyhook Technology (KECS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki TRaction Control (KTRC), Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS), Anti-lock Brake System (ABS), Kawasaki Engine Brake Control (KEBC), Kawasaki Quick Shifter (KQS) (dual direction), IMU-Enhanced Chassis Orientation Awareness

RENDIMIENTO

Suspensión delantera/recorrido del neumático	43mm inverted Showa fork with KECS-controlled rebound and compression damping, manual spring preload adjustability and top-out springs/4.7 in
Suspensión trasera/recorrido del neumático	Uni-Trak®, Showa BFRC lite gas-charged shock with piggyback reservoir, KECS-controlled compression and rebound damping electronically-adjustable spring preload/5.5 inspring/5.3 in

Neumático delantero	120/70-17
Neumático trasero	190/55-17
Frenos delanteros	Dual 320mm semi-floating discs with dual radial-mount, opposed 4-piston Brembo Stylema® calipers, Kawasaki Intelligent anti-lock Brake System (KIBS)
Frenos traseros	Single 250mm disc with opposed 2-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS)

DETALLES

Tipo de chasis	Trellis, high-tensile steel, with swingarm mounting plate
Ángulo de dirección/Avance	24.7° / 4.1 in
Largo total	85.6 in
Ancho total	31.1 in
Altura del asiento	49.6 in
Distancia al suelo	5.1 in
Altura del asiento	32.9 in
Peso en orden de marcha	590.9 lb*
Depósito de combustible	5.0 gal
Distancia entre ejes	58.3 in
Características especiales	Supercharged engine, 6.5" Full-color TFT Instrumentation, All-LED lighting including Cornering Lights, Kawasaki's Intelligent Proximity Activation Start System (KIPASS), Highly Durable Paint, Grip heaters, Tire Pressure Monitoring System (TPMS), Smartphone Connectivity via Kawasaki SPIN infotainment app
Colores disponibles	Emerald Blazed Green/Metallic Diablo Black/Metallic Matte Graphenesteel Gray
Garantía	12 Month Limited Warranty

Escanear con cámara para ver videos, características clave y más.



*La tara incluye todos los materiales y fluidos necesarios para su correcto funcionamiento, el depósito lleno de combustible (con una capacidad superior al 90 %) y el kit de herramientas (si está incluido).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI SE PREOCUPA: Lea el Manual de usuario y todas las advertencias del producto. Lleve siempre puesto un casco protección para los ojos, y ropa adecuada. Nunca conduzca bajo la influencia de las drogas o el alcohol. Cumpla con el programa de mantenimiento en su manual del propietario. ©2025 Kawasaki Motors Corp., U.S.A.

Las especificaciones están sujetas a cambios. Visite chile.kawasaki-la.com para obtener detalles completos del producto.